

# Check & Foot Valves



**Polypropylene Check Valves** 208

**PVC Check Valves** 208

**Brass Check Valves** 208

**Nylon Check Valves** 208

**Stainless Steel Check Valves** 208

**Foot Valves** 209

# Check & Foot Valves

## Mini Check Valves - Polypropylene



Part No.	Barbs
695-2B2B-B	1/8"
695-3B3B-B	3/16"
695-4B4B-B	1/4"

Also available with Viton, & EPDM seals

- Max press 8 Bar
- S/Steel spring - Buna seals
- Max temp 60°C
- Opening press 0.022 Bar

## PVC Check Valves



Part No.	Connections
426-4F4F-B	1/4" F x 1/4" F
426-4M4M-B	1/4" M x 1/4" M
426-4F4M-B	1/4" F x 1/4" M
426-4B4B-B	1/4" B x 1/4" B
426-6B6B-B	3/8" B x 3/8" B
426-8B8B-B	1/2" B x 1/2" B
426-4JG4JG	1/4" compression
426-6JG6JG	3/8" compression

- Max press 8 Bar
- Buna N seals
- Max temp 60°C
- Opening press 0.07 Bar

## 600 Series Polypropylene Check Valves



Part No.	Threads	Seals
685-8F8F-E	1/2" F	EPDM
685-8F8F-V	1/2" F	Viton
687-12F12F-E	3/4" F	EPDM
687-12F12F-V	3/4" F	Viton

- Max press 8 Bar
- S/Steel spring
- Max temp 60°C
- Opening press 0.07 Bar

## 800 Series Polypropylene Check Valves



Part No.	Threads
8206000	1 1/4" F x 1 1/4" F
8206001	1 1/2" F x 1 1/2" F
8206002	1 1/4" M x 1 1/4" M
8206003	1 1/2" M x 1 1/2" M

- Max press 10 Bar
- Buna seals
- 316 S/Steel spring
- Opening press 0.012 Bar

## Nylon Check Valves



Part No.	Threads
8369000	1/2" F x 1/2" F
8369001	3/4" F x 3/4" F
8369002	1" F x 1" F

- Max press 10 Bar
- Buna seals
- 316 S/Steel spring
- Opening press 0.012 Bar

## Nylon Foot Valve Filter



Part No.	Thread
8357000	1/2" F
8357001	3/4" F
8357002	1" F
8357003	1 1/4" F
8357004	1 1/2" F
8357005	2" F

- Max press 10 Bar
- Buna seals
- 316 S/Steel spring
- Opening press 0.012 Bar

## Brass Check Valves



Part No.	Threads
470-4F4F-B	1/4" F x 1/4" F
470-4F4M-B	1/4" F x 1/4" M
470-6F6F-B	3/8" F x 3/8" F
470-6F6M-B	3/8" F x 3/8" M

- Max press 200 Bar
- S/Steel ball
- Buna seals
- Max temp 70°C
- Opening press 0.07 Bar

## Stainless Steel Check Valves



Part No.	Thread	Lpm
60.2030.00	1/4" F x 1/4" F	25
60.2020.00	3/8" F x 3/8" F	40
60.2070.00	1/2" F x 1/2" F	80
60.2080.00	3/4" F x 3/4" F	180

- Max press 400 Bar
- Viton seals
- Max temp 90°C
- 303 Stainless steel
- Opening press 0.4 Bar

# Check & Foot Valves

## UD1 Series Check Valve

Part No.	Threads
<b>UD1</b>	3/4" M x 3/4" F

- Max press 200 Bar
- Max flow 180 Lpm
- Opening press 5 bar
- S/Steel & brass



## Check Valve M x F Threads

Part No.	Thread
<b>407-1010</b>	1/2"
<b>407-1011</b>	3/4"

- Conforms to CE standard



## Valve & Strainer

Items below can be combined to create a foot valve with filter



## Foot Valve & Strainer

Part No.	Thread
<b>402-1050</b>	1/2" F
<b>402-1051</b>	3/4" F
<b>402-1052</b>	1" F
<b>402-1053</b>	1 1/4" F
<b>402-1054</b>	1 1/2" F
<b>402-1055</b>	2" F

- Brass construction
- Max press 10 bar



## Brass Valve - Female Threads

Part No.	Thread	Bar
<b>407-1021</b>	3/8" F	16
<b>407-1022</b>	1/2" F	16
<b>407-1023</b>	3/4" F	16
<b>407-1024</b>	1" F	16
<b>407-1025</b>	1 1/4" F	10
<b>407-1026</b>	1 1/2" F	10
<b>407-1027</b>	2" F	10

- Brass construction
- Acetal copolymer disk with NBR gasket
- 302 S/Steel spring
- Max temp 80°C



## Stainless Steel Strainer

Part No.	Thread
<b>402-1010</b>	3/8" M
<b>402-1011</b>	1/2" M
<b>402-1012</b>	3/4" M
<b>402-1013</b>	1" M
<b>402-1014</b>	1 1/4" M
<b>402-1015</b>	1 1/2" M
<b>402-1016</b>	2" M

- 304 S/Steel screen with glass reinforced nylon threads
- 15 mesh screen

