

## Cleanmatic CL24V

Part No.	Volts	Lpm	Bar	Kg
<b>CL24V</b>	240	7	90	11.4

- 7 metre high pressure hose with 22mm coupling
- Trigger gun with 400mm extension lance
- Chemical induction bottle
- 2.5 metre power cable with moulded 13 amp plug
- Supplied with 13mm Ø screw connection inlet barb
- Current thermal overload protection
- 1.75Kw electric motor
- Dimensions 390L x 180W x 300H (mm)



## Cleanmatic CL24RK

Part No.	Volts	Lpm	Bar	Kg
<b>CL24RK</b>	240	7	160 (EWE)	12.2

EWE - 'Equivalent Washing Effect' of rotary nozzle head. Pump pressure = 90 Bar.

- 7 metre high pressure hose with 22mm coupling
- Trigger gun with 400mm extension lance
- Chemical induction bottle
- 2.5 metre power cable with moulded 13 amp plug
- Supplied with 13mm Ø screw connection inlet barb
- Current thermal overload protection
- 1.75Kw electric motor
- Dimensions 520L x 225W x 360H (mm)



## Boxjet & Turbo15

Part No.	Volts	Lpm	Bar	Kg
<b>Boxjet</b>	240	8	70	18.5
<b>Turbo 15</b>	110	8	55	18.5

- Ceramic plungers
- Motor protection to IP55
- Thermal cut out protection
- Flow 8 Lpm - Press up to 70 Bar
- 1.5Hp electric motor
- Hose length 8 metres
- Dimensions 362L x 240W x 235H (mm)



## Quicky

Part No.	Volts	Lpm	Bar	Kg
<b>Quicky</b>	240	10	100	28

- Ceramic plungers
- Motor protection to IP55
- Thermal cut out protection
- Flow 10 Lpm - Press 100 Bar
- 2.5Hp electric motor
- Hose length 8 metres
- Dimensions 405L x 240W x 235H (mm)



## IP Range of Electric Cold Water Pressure Washers

Part No.	Bar	Lpm	Kw	Volts	Chemicals	Manifold	Kg
<b>IP8130M</b>	130	8	2.2	240V 1Ph	9.5 Lts	Aluminium	22
<b>IP9130M</b>	130	9.5	3	240V 1Ph	9.5 Lts	Brass	25

- Auto stop/start for prolonged life & reduced power consumption
- 8 metre high pressure hose
- Adjustable chemical injection
- Lance, hose and power cable storage facilities
- Pressure gauge fitted as standard
- Motor protection to IP55 standard
- Current thermal overload protection
- Dimensions 550L x 400W x 760H (mm)

**AUTO  
STOP  
START**

