

Vacuum Cleaners & Spray Extractors

Skip Wet



Part No.	Watts	Dry	Wet	Hose	Dimensions mm	Kg
SKIP WET	1200	17 Lts	9 Lts	32mm	395D x 395W x 535H	7
10 metre power cable - 2 metre suction hose - 240 Volts						



With its powerful 1200 watt motor, light weight and generous capacity, the Skip Wet is ideally suited for domestic and light commercial use.

The Skip Wet is supplied with a comprehensive range of tools to ensure excellent results on a variety of surfaces.



Pony - Spray Extractor



Part No.	Watts	Dry	Wet	Extraction	Solution	Pump Press	Hose	Kg
PONY	1200	22 Lts	10 Lts	10 Lts	6.2 Lts	2 Bar	32mm	10
Dimension 385D x 385W x 620H								
10 metre power cable - 2.5 metre suction hose - 240 Volts								




- Pressure activated detergent pump for automatic stop/start operation.
- Rust free S/Steel tanks for light weight, mobility & strength.
- 10 metre power supply cable.
- Comprehensive accessory kit.
- Operate from 230 Volt single phase power supply.
- High performance heavy-duty two stage by-pass vacuum motors.



Garage - Spray Extractor



Part No.	Watts	Dry	Wet	Extraction	Solution	Pump Press	Hose	Kg
GARAGE	2x1200	60 Lts	40 Lts	40 Lts	25 Lts	2 Bar	38mm	26
Dimension 700D x 600W x 910H								
10 metre power cable - 2.5 metre suction hose - 240 Volts								



- Pressure activated detergent pump for automatic stop/start operation.
- Rust free S/Steel tanks for light weight, mobility & strength.
- 10 metre power supply cable.
- Comprehensive accessory kit.
- Operate from 230 Volt single phase power supply.
- High performance heavy-duty two stage by-pass vacuum motors.



Hippo Spray Extractor



Part No.	Watts	Dry	Wet	Extraction	Solution	Pump Press	Hose	Kg
HIPPO	1200	27 Lts	12 Lts	12 Lts	6.2 Lts	2 Bar	32mm	9.5
Dimensions 390D x 390W x 565H								
10 metre power cable - 2 metre suction hose - 240 Volts								



Hippo is supplied with a comprehensive range of tools for both **wet and dry** use.

With its powerful 1200-watt by-pass vacuum motor and 48 watt solution pump, the Hippo offers exceptional performance and value for money.



ISSA Junior Series - Dry - 240 Volts

Part No.	Watts	Lts	Hose	Kg
JUNIOR 103	1200	16	32mm	8.5
Dimensions 385D x 385W x 552H				



- Heavy-duty chromed steel tanks.
- Operate from 240 Volt single phase power supply.
- Two stage by-pass motors on all wet/dry models.
- 10 metre power supply cable.
- Impact resistant polypropylene bumper skirts.
- 2 metres suction hose



ISSA Supercondor - Wet & Dry - 240 & 110 Volts

Part No.	Watts	Dry	Wet	Hose	Kg
SUPERCONDOR J	1200	16 Lts	7.5 Lts	32mm	8.5
Dimensions 385D x 385W x 535H					
SUPERCONDOR I	1200	26 Lts	15 Lts	32mm	9
SUPERCONDOR I (110V)	1200	26 Lts	15 Lts	32mm	9
Dimensions 465D x 465W x 610H					



- Heavy-duty chromed steel tanks.
- 240 or 110 Volt single phase power supply.
- Two stage by-pass motors on all wet/dry models.
- 10 metre power supply cable.
- Impact resistant polypropylene bumper skirts.
- Anti-foaming system on all wet models.
- 2 metres suction hose



ISSA 515 Series - Wet & Dry - 240 & 110 Volts

Part No.	Watts	Dry	Wet	Hose	Kg
ISSA 515M	1200	38 Lts	26 Lts	38mm	10
ISSA 515M (110V)	1200	38 Lts	26 Lts	38mm	10
Dimensions 465D x 465W x 765H					



- Heavy-duty chromed steel tanks.
- 240 or 110 Volt single phase power supply.
- Two stage by-pass motors on all wet/dry models.
- 10 metre power supply cable.
- Impact resistant polypropylene bumper skirts.
- Anti-foaming system on all wet models.
- 2.5 metres suction hose



ISSA 640 Series - Wet & Dry - 3 Motors - 240 & 110 Volts

Part No.	Watts	Dry	Wet	Hose	Kg
ISSA 640M	3x1200	78 Lts	55 Lts	38mm	28
ISSA 640M (110V)	3x1200	78 Lts	55 Lts	38mm	28
Dimensions 700D x 570W x 930H					



- Heavy-duty chromed steel tanks.
- 240 or 110 Volt single phase power supply.
- Two stage by-pass motors on all wet/dry models.
- 10 metre power supply cable.
- Impact resistant polypropylene bumper skirts.
- Anti-foaming system on all wet models.
- Fitted as standard on a tipping trolley.
- 2.5 metres suction hose



ISSA 629 with Submersible Pump - 2 Motors

Part No.	Watts	Volts	Wet	Hose	Kg
ISSA629MSUB	2x1200	240	80 Lts	38mm	28
Dimensions 700D x 570W x 930H					



Based on the ISSA series the 629SUB has an internal submersible pump to allow the tank to be easily emptied. It can also be used continuously when the vacuum is in operation.

The pump has a flow rate of 200 Lpm, 7 metre head, power consumption of 550W & is fitted with an automatic float switch. The outlet is mounted on the side of the tank & has a 1" Ø hose barb.

Internal
Submersible
Pump

