

# Data Sheet

(anti graffiti coating)

**NU-CRYL® A.G.**

## DESCRIPTION:

Nu-Cryl A.G. is a unique, clear, hydrophobic acrylic coating system.

## ADVANTAGES:

Nu-Cryl A.G. will not noticeably change the appearance of the substrate. Due to its excellent stain resistant and water repellent qualities, dirt, pollution, and even graffiti can be removed from the treated surface. The system gives long life graffiti and environmental protection. It has outstanding resistance to weathering and ultra-violet degradation, and no reapplication is required after graffiti removal. Satisfies Class'0' requirements of current Building Regulation.

## USES:

For use on brickwork, concrete, natural stone, reconstructed stone and blockwork, marble and terrazzo. Compatible with concrete surfaces treated with Silane. Allow 72 hours to lapse before overcoating surfaces treated with Silane.

**COLOUR RANGE:** Colourless      Moisture vapour permeable

## COVERAGE RATE:

This is dependant on texture and porosity of the substrate. The figures quoted below are given only as guidance.

Granite.....15m<sup>2</sup>/Ltr  
Marble.....13m<sup>2</sup>/Ltr  
Block paving.....8m<sup>2</sup>/Ltr  
Engineering brickwork...8m<sup>2</sup>/Ltr  
Concrete.....5m<sup>2</sup>/Ltr  
Facing brickwork.....5m<sup>2</sup>/Ltr  
Concrete blockwork...3m<sup>2</sup>/Ltr  
Self coloured render.....3m<sup>2</sup>/Ltr

## DRYING TIME:

Touch dry:1-2 hours.      Overcoat:Immediately after the first application.      Fully dry:24 hours.

**PREPARATION:**      Ensure surface to be treated are clean, free from contamination and dry.

## APPLICATION:

Application by low pressure spray or by brush/roller taking care to avoid any sagging. One application is normally required, however on porous substrates a second application may be required. Apply the second application in the same manner immediately after the first application, taking care not to allow the first application to dry out.

## EQUIPMENT CARE:

All equipment should be cleaned with water immediately after use.

## STORAGE:

Store away from direct sunlight and sources of heat. Protect from frost.

**SHELF LIFE:** 6 months (in original sealed container).

**HEALTH & SAFETY:** Refer to health and safety sheets.

The information contained on here & on other Data Sheets / MSDS Sheets is based on the present state of knowledge and current national legislation. It provides guidance on health, safety and environmental aspects of the products and should not be construed as any guarantee of technical performance or suitability for particular applications. The responsibility to ensure safe working conditions within the workplace remains with the user. The health hazard and general information contained within Material Safety Data Sheet are given as a guide to the precautions required maintaining a safe work environment.

*Malcolm Smith – Power Cleaning*

*45 Roundponds, Melksham, Wiltshire. SN12 8DW*

*Tel: 01225 707200 / Mobile: 07850 119990*

[sales@malcleanse.co.uk](mailto:sales@malcleanse.co.uk)

[www.powerwashinguk.co.uk](http://www.powerwashinguk.co.uk)

[www.malcleanse.co.uk](http://www.malcleanse.co.uk)